

Perma-Seal Terminals and Splices >

Perma-Seal Terminals and Splices provide a rugged, environmentally sealed connection that insulates, protects and seals electrical connections from physical abuse, water, salt and other corrosive compounds, and are ideal for use in a wide variety of harsh environments.

ADVANTAGES AND FEATURES

Provides securely sealed electrical connections

Engineered to offer a long-lasting connection resistant to water, salt, condensation, corrosion and heat

Simplifies and speeds installation

Heat-sensitive insulation shrinks at a lower temperature (90°C) and up to 40% quicker than many competing products, making installation faster and easier

Helps guard against mechanical damage

Rugged proprietary NiAc adhesive-lined heat-shrinkable insulation sleeve resists abrasion and cutting, helping maintain insulating and sealing properties both inside and out

Enables simple visual inspection

See-through insulation allows for easy visual inspection of crimped and sealed joints

Current (max.)	Up to 50.0A (varies by wire size)
Voltage (max.)	600V
Wire Size	8 to 22 AWG, 8.50 to 0.35mm ²
Terminal Styles	Ring, Spade, Quick Disconnect
Minimum Shrink Temperature	90°C
Operating Temperatures	-55 to +125°C

Offers versatility for a variety of applications

Heat-shrinkable sleeve has a funnel entry opening and can shrink to less than half its original diameter, enabling it to accommodate both thick and thin wire insulation inside and out

Repels moisture incursion

Hot-melt adhesive lining the inside of the insulation melts during heat-shrinking and fills voids in the joint, helping seal the connection and repelling moisture incursion, even during pressure cycling

Resists chemical damage

Excellent chemical-resistant properties protect against damage even when submerged in antifreeze, brake fluid, gasoline, motor oil, isopropanol, trichloroethylene, diesel fuel, salt water or battery acid



Perma-Seal Terminals and Splices >

APPLICATIONS

Commercial Vehicle

Marine components
Bilge pumps and water pumps
Construction vehicle harnesses
Tractors and lawn/garden equipment
Agricultural machinery

Automotive Aftermarket


Gauges
Control unit modules
Battery packs
Body electronics

Consumer

Pool and spa components
HVAC compressors
Lawn and garden equipment
Snow blowers
Liquid-dispensing equipment



Construction Vehicle Harnesses



Body Electronics



Pool and Spa Components

SPECIFICATIONS

Reference Information

Packaging: Box or Mylar tape on reels
UL File No.: E32244
CSA File No.: LR18689
Wire Size: 8 to 22 AWG
8.50 to 0.35mm²
Stud Size: #6 to .5"

Electrical

Voltage (max.): Up to 600V
Amperage (max.): Up to 50.0A (varies by wire size)
Dielectric Strength: 750V/mil (30KV/mm)

Physical

Terminal Material: Copper or Brass
Plating: Matte Tin
Insulation Materials:
NiAc adhesive-lined heat shrinkable
Operating Temperatures: -55 to +125°C

www.molex.com