



Features

- Semi-shielded construction
- Inductance range: 0.5 to 330 μ H
- Rated current up to 12 A
- AEC-Q200 qualified
- RoHS compliant* and halogen free**

Applications

- Automotive systems:
 - Driver assistant
 - Infotainment
 - Lighting
- DC/DC converters
- Power supplies
- Digital video cameras
- HDDs
- Smartphones
- Televisions, LCD displays

SRN8040TA Series - Semi-shielded Power Inductors

Electrical Specifications @ 25 °C

Bourns Part No.	Inductance @ 1 MHz / 1 V		Q (Min.) @ 1 MHz	SRF (MHz) Typ.	DCR (m Ω) ± 20 %	Irms (A) Max.	Isat (A) Max.
	L (μ H)	Tol. %					
SRN8040TA-R50Y	0.5	± 30	20	165	5.5	12.00	17.00
SRN8040TA-1R0Y	1.0	± 30	15	85	8.2	8.50	13.80
SRN8040TA-1R4Y	1.4	± 30	15	78	10	8.20	11.80
SRN8040TA-1R5Y	1.5	± 30	15	66	10	8.00	11.50
SRN8040TA-2R2Y	2.2	± 30	15	57	11.5	7.40	9.80
SRN8040TA-3R3Y	3.3	± 30	15	48	15	6.60	8.00
SRN8040TA-4R7M	4.7	± 20	15	38	19.5	5.80	6.70
SRN8040TA-5R6M	5.6	± 20	15	33	22	5.40	6.20
SRN8040TA-6R8M	6.8	± 20	15	29	25	5.10	5.60
SRN8040TA-100M	10	± 20	15	25	33	4.60	5.00
SRN8040TA-150M	15	± 20	12	20	50	3.60	4.00
SRN8040TA-220M	22	± 20	12	18	73	2.90	3.10
SRN8040TA-330M	33	± 20	12	15	100	2.30	2.60
SRN8040TA-470M	47	± 20	12	12	135	2.00	2.20
SRN8040TA-560M	56	± 20	12	10.5	160	1.75	1.90
SRN8040TA-680M	68	± 20	12	9.5	205	1.65	1.75
SRN8040TA-820M	82	± 20	12	8.5	230	1.40	1.60
SRN8040TA-101M	100	± 20	10	8	300	1.20	1.45
SRN8040TA-121M	120	± 20	10	7.5	350	1.10	1.30
SRN8040TA-151M	150	± 20	10	7	410	0.98	1.20
SRN8040TA-181M	180	± 20	10	6.5	490	0.91	1.04
SRN8040TA-221M	220	± 20	10	5.5	610	0.85	0.99
SRN8040TA-331M	330	± 20	10	5	850	0.70	0.75




General Specifications

Operating Temp. -55 °C to +125 °C
(Temperature rise included)
Storage Temperature ... -55 °C to +125 °C
Temperature Rise 40 °C at rated Irms
Rated Current
..... Inductance drops 30 % at Isat
Failure In Time (FIT) 24.7/10⁹ hours
Mean Time Between Failures (MTBF)
..... 40.4 x 10⁶ hours

Materials


Core Ferrite
Wire Enameled copper
Terminal Finish Sn
Coating Magnetic epoxy resin
Packaging 1000 pcs. per 13-inch reel

Product Dimensions



DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

Electrical Schematic




How to Order

SRN8040TA - 100M

Model _____
Value Code (see table) _____

Recommended Layout



DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

**Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.


Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.

Users should verify actual device performance in their specific applications.





SRN8040TA Series - Semi-shielded Power Inductors

BOURNS®

Temperature Rise vs. Current



Inductance vs. Current




Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.


SRN8040TA Series - Semi-shielded Power Inductors

BOURNS®

Soldering Profile



Packaging Specifications



USER DIRECTION OF FEED
QTY: 1000 PCS. PER REEL

DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$