

LibAXDSP (AX8052 DSP Library) Software Manual



ON Semiconductor®

www.onsemi.com

APPLICATION NOTE

Introduction

LibAXDSP is a library providing optimized digital signal processing functions. It contains the following features:

- Finite Impulse Response Filters (signed $16 \times 16 \rightarrow 32$)
- CORDIC (16 bit)

LibAXDSP is available in source and binary form for SDCC, Keil C51 and IAR ICC.

Evaluation Board Peripherals

LIBAXDSP.H

libaxdsp.h contains the Digital Signal Processing routines.

- VOID CORDIC16_VECN(STRUCT CORDIC16 *C)

This function computes the first N stages of a 16 bit angular CORDIC algorithm in vectoring mode. The structure pointed to by c contains both the input and output values. It computes:

$$x_{out} \leftarrow k_N \cdot \sqrt{x_{in}^2 + y_{in}^2}$$

$$y_{out} \leftarrow \approx 0$$

$$P_{out} \leftarrow P_{in} + \frac{2^{15}}{\pi} \cdot \arctan\left(\frac{y_{in}}{x_{in}}\right)$$

The most accurate result is obtained with $N = 15$. Lower N result in faster but less accurate computation. The scaling constant k_N depends on the number of stages (see table):

N	k_N	N	k_N	N	k_N
		6	1.64669325427364	11	1.64676019268469
2	1.62980060130066	7	1.64674350659690	12	1.64676024176197
3	1.64248406575224	8	1.64675607020488	13	1.64676025403129
4	1.64568891575725	9	1.64675921113982	14	1.64676025709862
5	1.64649227871248	10	1.64675999637562	15	1.64676025786545

AND9380/D

- VOID CORDIC16_ROT(`STRUCT CORDIC16 *C`)

This function computes the first N stages of a 16 bit angular CORDIC algorithm in rotation mode. The structure pointed to by `c` contains both the input and output values. It computes:

$$x_{out} \leftarrow k_N \cdot \left[x_{in} \cdot \cos\left(\frac{P_{in} \cdot \pi}{2^{15}}\right) - y_{in} \cdot \sin\left(\frac{P_{in} \cdot \pi}{2^{15}}\right) \right]$$

$$y_{out} \leftarrow k_N \cdot \left[x_{in} \cdot \sin\left(\frac{P_{in} \cdot \pi}{2^{15}}\right) + y_{in} \cdot \cos\left(\frac{P_{in} \cdot \pi}{2^{15}}\right) \right]$$

$$P_{out} \leftarrow \approx 0$$

The most accurate result is obtained with $N = 15$. Lower N result in faster but less accurate computation. The scaling constant k_N depends on the number of stages (see table):

N	k_N	N	k_N	N	k_N
		6	1.64669325427364	11	1.64676019268469
2	1.62980060130066	7	1.64674350659690	12	1.64676024176197
3	1.64248406575224	8	1.64675607020488	13	1.64676025403129
4	1.64568891575725	9	1.64675921113982	14	1.64676025709862
5	1.64649227871248	10	1.64675999637562	15	1.64676025786545

- INT32_T FIR_XI16_XI16(`CONST INT16_T __XDATA *P0, CONST INT16_T __XDATA *P1, UINT16_T LEN`)
INT32_T FIR_XI16_CI16(`CONST INT16_T __XDATA *P0, CONST INT16_T __CODE *P1, UINT16_T LEN`)

These functions compute a signed $16 \times 16 \rightarrow 32$ bit finite impulse response filter.

ON Semiconductor and the  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local Sales Representative