

AX8052 Power On Reset



ON Semiconductor®

www.onsemi.com

APPLICATION NOTE

Introduction

This application note discusses designing power-on reset for the AX8052F1xx family of microcontrollers for a wide range of supply voltage conditions. After explaining why a Power-on-Reset (POR) circuit can fail, this application note covers the best ways to make POR work reliably.

Causes

The AX8052 microcontroller features a built-in Power-On Reset circuit which does not draw current except for negligible leakage. This ultra-low-power consumption is possible because the internal POR circuitry is edge sensitive. Therefore certain rise and fall times of the supply voltage (VDD_IO) are required to trigger the internal POR:

1. Supply voltages starting below 0.1 V with rise and fall times faster than 0.1 V/ms (normal start-up)
2. Supply voltages starting between 0.1 V and 0.7 V with the rise and fall times faster than 3.3 V/ms (fast voltages)

For other cases an external reset circuit is strongly recommended.

Operation of the device in the voltage range from 0.4 V to 0.8 V without proper reset can cause flash memory loss.

Normal Start-up

Figure 1 depicts the VDD_IO waveform for a normal start-up. VDD_IO should start at 0.1 V maximum, and then rise with a slope of at least 0.1 V/ms, to the normal operating voltage.




Figure 1. Normal Start-up

If either the maximum start voltage or the slope requirement cannot be met, Axsem recommends the use of external reset circuitry or an external reset device.

Temporary Loss of Power

Figure 2 shows a temporary loss of power waveform. In this scenario, if the VDD_IO voltage does not return to below 0.1 V before reapplying power again, but lingers in the range of approximately 0.45 V to 0.7 V and the rise time is lower than 3.3 V/ms then external reset circuitry or an external reset device should be used.




Figure 2. Temporary Loss of Power

Power Management Interrupt

Axsem recommends to use power management interrupt code similar to the example given below. The power management interrupt is triggered by the voltage of VDD_IO falling below brown-out threshold, and then puts the microcontroller into standby mode.

```
void pwrmgmt_irq(void) __interrupt(6)
{
    uint8_t pc = PCON;
    if (!(pc & 0x80))
        return;
    GPIOENABLE = 0;
    IE = EIE = E2IE = 0;
    for (;;)
        PCON |= 0x01;
}
```

The interrupt needs to be enabled (IE_6 = 1; EA = 1;). If the application firmware uses bus master peripherals (like DMA or AES), these peripherals should be shut down in the brownout interrupt as well.

The interrupt protects the circuit from the microcontroller potentially executing arbitrary instructions. The interrupt is effective if the falling slope of VDD_IO is slower than approximately 1 V/ms; otherwise, the remaining time is not sufficient to detect the brown-out condition and to handle the interrupt.

External Reset Circuit

A reset circuit like the one shown in Figure 3 is suitable to handle difficult power supply situations. The voltage across the zener diode and the turn-on voltage of Q1 are kept constant regardless of VDD_IO. RESET_N is decided as follows:

$$\text{RESET_N} = \text{VDD_IO} \text{ if } \text{VDD_IO} > \text{VZD1} + \text{VONQ1}$$

$$\text{RESET_N} = \text{GND} \text{ if } \text{VDD_IO} < \text{VZD1} + \text{VONQ1}$$




Figure 3. Standard Reset Circuit

Alternatively external voltage supervisors and reset generators can be used. Suitable circuits include the Rohm Semiconductors BU4211G or BU4811G.

Conclusion

POR is a difficult issue to manage. Many unpredictable events can influence the circuitry. A power interruption might not happen often but it can at any time. For many common cases, the AX8052 internal power-on reset circuit ensures reliable start-up and no external components are required. Some corner cases, however, such as temporarily losing power, may require an external reset circuit.

ON Semiconductor and the  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
 Literature Distribution Center for ON Semiconductor
 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
 USA/Canada
Europe, Middle East and Africa Technical Support:
 Phone: 421 33 790 2910
Japan Customer Focus Center
 Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
 For additional information, please contact your local Sales Representative