

# STM32G0 SERIES

# 32-bit Mainstream MCUs



# Entry-level Arm® Cortex®-M0+ Microcontrollers - Efficiency at its best

The STM32G0 Series is not simply another Arm® Cortex®-M0+ MCU. It is setting a new definition of what an efficient microcontroller must offer. This is all about best optimization, down to each and every detail, to offer the best value for money and allow you to achieve your goals with the minimum BOM cost and the maximum flexibility for upgrades. The STM32G0x0 Value Line embeds an accurate internal clock allowing further cost saving, and makes no compromise on what matters. The STM32G0x1 line provides upgraded features in analog, timer resolution up to 2xfcpu (7.8ns) and is IoT ready with enhanced security features. It supports FDCAN, USB crystal-less and the latest USB type-C specification including Power Delivery 3.0.

### **EFFICIENT**

- Arm® Cortex® M0+ at 64 MHz
- Compact cost: maximum I/Os count
- Best RAM/Flash Ratio
- Smallest possible package down to 8-pin
- Large platform up to 512 Kbytes Flash in small packages
- 500 nA in standby with RTC, 3.5 μA in stop mode, <100 μA/MHz
- Accurate internal high-speed clock 1% RCI
- Offers the best value for money
- Free tool suite

#### **ROBUST**

- Low electromagnetic susceptibility, EMC
- Clock Monitoring and 2 Watchdogs
- Voltage monitoring with interrupts and reset
- Error correction on Flash, parity on RAM
- IoT ready with embedded security
- Hardware AES-256 encryption
- Safe Firmware upgrade / Install

## **SIMPLE**

- Easy to configure thanks to the intuitive and graphic STM32CubeMX configuration tool.
- Easy to develop based on the Hardware Abstraction Layer library (HAL) or the lowlayer library (LL) allowing maximum re-use and faster

# STM32G0C1 block diagram

#### System Connectivity Arm® Cortex®-M0+ CPU Up to 64 MHz 3x SPI (I2S) Power supply lested vector interrupt POR/PDR/PVD/BOR **6x USART** Controller (NVIC) (3x with LIN, smartcard, Xtal oscillator IrDA, modem control) SW debug 32 kHz + 4 to 48 MHz 2x LPUART Memory Protection Unit Internal RC oscillators 32 kHz (±5%) AHB-Lite bus matrix **Fast Mode Plus** + 16 MHz (±1%) (2x SMBus, PMBus) APB bus Internal RC oscillator 2x FDCAN 48 MHz (auto trimming on Up to 512-Kbyte ext. synchro) Flash memory USB FS 2.0 Device (crystal less) PLL + Prescaler Up to 144-Kbyte SRAM Host Clock control **Boot ROM USB Power Delivery** (incl. BMC + PHY) RTC/AWU 12-channel DMA Systick timer 2x watchdogs Control **Analog** (independent and window) 1x 32-bit timer Temp. sensor 94 I/Os on 100 pins 1x 16-bit Motor C. timer 1x 12-bit ADC SAR Cyclic redundancy check $f_{MAX} = 128 \text{ MHz}$ 6-channels / 2.5 MSPS (CRC) 4 PWM + 3 compl. 1x 12-bit DAC 2ch 6x 16-bit timers **Encryption** one with $f_{MAX} = 128 \text{ MHz}$ 3x comparators **AES (256-bit)** 2x Low-power timers **True RNG**

#### **Hardware Tools**

A full set of evaluation boards enables flexible prototyping as well as full STM32G0 evaluation.





STM32G081B-EVAL STM32G0C1E-EV Evaluation boards

STM32G0316-DISC0 / STM32G071B-DISC0 (USB Type-C™) **Discovery Kits** 





NUCLEO-G031K8 (32-pin Nucleo)

NUCLEO-G070RB / NUCLEO-G071RB NUCLEO-G0B1RE (64-pin Nucleo)


### **Software Tools**

STM32CubeMX enables fast development thanks to its MCU clock configurator, power consumption calculator and code generation tools

#### **Embedded Software**

The STM32CubeG0 package includes the STM32Cube HAL and low-layer (LL) APIs peripheral drivers, plus a consistent set of middleware components (RTOS, USB, USB Power Delivery, FatFS, graphics and STM32 touch sensing). All embedded software utilities come with a full set of examples running on ST boards.

# STM32G0 portfolio



© STMicroelectronics - June 2021 - Printed in United Kingdom - All rights reserved ST and ST logo are trademarks or registered trademarks of STMicroelectronics International NV or its affiliates in the EU and/or other countries. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

