



## POTTER & BRUMFIELD POWER PCB RELAY T9S

TE Connectivity (TE)'s Potter & Brumfield Power PCB relay T9S series is primarily designed for electrical vehicle charging stations, power supply and for photovoltaic inverter applications. The extended contact gap (> 2.1 mm) of this relay provides improved isolation and dielectric strength, which enables usage in high elevation environment. The Potter & Brumfield Power PCB relay T9S is a high performing quality relay, that is safe and reliable.

### BENEFITS

- Enables customer power-upgraded inverters, power supply or other equipment to switch successfully and safely
- High carrying capability with small space saving size
- Low temperature rise and energy loss by PWM or low voltage holding

### KEY FEATURES

- 1.5mm/1.8mm/2.1mm contact gap version for selection
- Low temperature rise
- High switching capability at 40A

# Potter & Brumfield Power PCB relay T9S

## APPLICATIONS

- Electrical vehicle charging
- Photovoltaic inverter
- Power Supply
- Electrical vehicle

## MATERIALS

- Ag alloy (Cd free)

## ELECTRICAL

- 35A, 277VAC, resistive, 50k cycles
- 40A, 30VDC, resistive, 60k cycles
- 40A, 250VAC, resistive, 20k cycles

## MECHANICAL

- PCB Terminal

## SPECIFICATIONS

- -40°C-105°C
- Contact gap >1.5mm/1.8mm/2.1mm

## STANDARDS

- IEC 61810-1
- UL508, GB/T 21711.1

## Part Number List

Product code	Version	Contact arrangement	Contact material	Contact gap	Coil	Part Number
T9SV1K18-12T	PCB, flux proof	1 form A (NO) contact	Ag alloy	>2.1mm	12VDC	<a href="#">2027395-7</a>
T9SV1K15-12				>1.5mm		<a href="#">2027395-1</a>
T9SV1K15-12S				>1.8mm		<a href="#">2027395-3</a>

## te.com

© 2020 TE Connectivity. All Rights Reserved.

Potter & Brumfield, TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks owned or licensed by TE Connectivity. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

2-1773984-8 08/20 AK